

TECHNICAL DATA SHEET



Secury360 Box V3 + LTE

You don't build a castle on sand. You need a strong foundation. That's why the S360 box contains the best hardware, which can also run your VMS all at once. So you don't need an extra PC in your setup!



Technical data	WITHOUT HD	WITH 2,5" HD	WITH 3,5" HD
Dimensions	217mm x 75mm x 247mm		
Weight	1,90 kg	2,22 kg	2,48 kg
I/O inputs			
Number	6		
Type	15VDC, galvanic isolated, to be used with a voltage-free contact		
Connector type	2 x 4 pole plugable connector. Common ground.		
Wire range	1.5mm ² / stranded or solid		
Wire strip length	6 - 7mm		
I/O outputs			
Number	6		
Type	Voltage-free relay contact		
Contact type	1A, 220 VDC/250 VAC		
Connector type	4 x 6 pole plugable connector		
Wire range	1.5mm ² / stranded or solid		
Wire strip length	6 - 7mm		
Power supply			
Input voltage	12V ... 24V		
Maximum input current	1.0A	1.3A	2.1 A (3)
Maximum input power	12W	15.6W	25.2W
General			
EMC immunity/emission	EN50130-4		
Storage temperature	-40°C ... +85°C		
Operation temperature	-20°C ... 65°C	-20°C ... 65°C	-20°C ... 55°C (1)
Relative humidity	95%, no condensation		
Protection rating	IP30		
Assembly	No addition	2.5" assembly kit	3.5" assembly kit
LTE			
Brand	SIMCom SIM7600SA-H-PCIE		
Data transfer	LTE: 150 Mbps DL - 50 Mbps UL		
	HSPA+: 42 Mbps DL - 5,76 Mbps UL		
	WCDMA: 384 Kbps DL - 384 Kbps UL		
	GPRS/EDGE: 236,8 Kbps DL - 236,8 Kbps UL		
Protocol	TCP/IP/IPV4/IPV6/Multi-PDP/FTP/FTPS/HTTP/HTTPS/DNS		

(1) Only guaranteed with the use of the fan extension module

(2) Weight without HD mounted

(3) With 3.5" WD800IPURP HD